

SAFETY DATA SHEET

PRODUCT: SCOOT

Page 1

SECTION 01: PRODUCT AND COMPANY INFORMATION

MANUFACTURER/SUPPLIER	LES INVESTISSEMENTS B.S.C. INC.
MANUFACTURER'S/SUPPLIERS ADDRESS.....	109 IBER RD., UNIT #3, OTTAWA, ON K2S 0X5 613-744-8896
PRODUCT NAME	SCOOT
PRODUCT USE	GLASS CLEANER
EMERGENCY PHONE NUMBER.....	CANUTECH 613-996-6666

SECTION 02: HAZARDS IDENTIFICATION



ROUTE OF ENTRY:	
SKIN CONTACT	NOT A PRIMARY SKIN IRRITANT AFTER EXPOSURE OF SHORT DURATION.
SKIN ABSORPTION	N.AV.
EYE CONTACT.....	IRRITATING TO EYES. EXPOSURE TO HIGH VAPOUR CONCENTRATIONS MAY CAUSE EYE IRRITATION.
INHALATION.....	EXPOSURE TO HIGH VAPOUR CONCENTRATIONS MAY CAUSE RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS, NAUSEA, INCOORDINATION, DROWSINESS AND LOSS OF CONSCIOUSNESS.
INGESTION	ALTHOUGH INGESTION IS UNLIKELY, LIQUID WOULD IRRITATE UPPER DIGESTIVE TRACT IF SWALLOWED. INGESTION OF THIS PRODUCT MAY CAUSE HEADACHE, DIZZINESS, FATIGUE AND CENTRAL NERVOUS SYSTEM DEPRESSION.
EFFECTS/SYMPTOMS OF ACUTE EXPOSURE	EXPOSURE MAY OCCUR VIA INHALATION, INGESTION, SKIN ABSORPTION AND SKIN OR EYE CONTACT.
EFFECTS/SYMPTOMS OF CHRONIC EXPOSURE	PROLONGED AND REPEATED CONTACT WITH SKIN CAN CAUSE DEFATTING AND DRYING OF THE SKIN RESULTING IN SKIN IRRITATION AND DERMATITIS.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE.....	PRE-EXISTING EYE, SKIN AND RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS HAZARDS IDENTIFICATION

HAZARDOUS INGREDIENTS	C.A.S. #	%	TLV	LD50	LC50
ISOPROPYL ALCOHOL	67-63-0	1 - 5	ACGIH: 400 PPM STEL; 200 PPM TWA. OSHA: 400 PPM TWA; 980 MG/M3 TWA; 1225 MG/M3 STEL; 500 PPM STEL. IDLH: 2000 PPM.	12800 MG/KG (DERMAL, RABBIT) 3600 MG/KG (ORAL, MOUSE) 5045 MG/KG (ORAL, RAT)	12000 PPM/8H (IHL, RAT)

SECTION 04: FIRST AID MEASURES

SKIN CONTACT	FLUSH AFFECTED SKIN WITH GENTLY FLOWING LUKEWARM WATER FOR AT LEAST 20 MINUTES. REMOVE CONTAMINATED CLOTHING WHILE RINSING. WASH CONTAMINATED SKIN WITH MILD SOAP AND WATER FOR 15 MINUTES. IF IRRITATION OCCURS AND PERSISTS, OBTAIN MEDICAL ATTENTION.
EYE CONTACT.....	FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. OBTAIN MEDICAL ATTENTION AS SOON AS POSSIBLE AFTER FIRST AID HAS BEEN INITIATED AND COMPLETED.
INHALATION.....	REMOVE VICTIM FROM FURTHER EXPOSURE AND RESTORE BREATHING, IF REQUIRED. OBTAIN MEDICAL ATTENTION.
INGESTION	DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON. GUARD AGAINST ASPIRATION INTO LUNGS BY HAVING THE INDIVIDUAL TURN ON TO

NOTES TO PHYSICIAN.....

THEIR LEFT SIDE. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. OBTAIN MEDICAL ATTENTION IMMEDIATELY. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCURS BEFORE VOMITING, GASTRIC LAVAGE WITH A CUFFED ENDOTRACHEAL TUBE SHOULD BE CONSIDERED. METABOLISM OF ISOPROPANOL FORMS ACETONE, WHICH MAY BE DETECTED IN THE URINE AND EXPIRED AIR. IN CONTRAST TO DIABETIC ACIDOSIS, ACIDOSIS WILL OCCUR IN THE ABSENCE OF HYPERGLYCEMIA. HEMODIALYSIS SHOULD BE CONSIDERED IN SEVERE ACUTE INTOXICATIONS.

SECTION 05: FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY
 MEANS OF EXTINCTION/EXTINGUISHING MEDIA: ..
 FLASH POINT.....
 UPPER FLAMMABLE LIMIT (% BY VOLUME).....
 LOWER FLAMMABLE LIMIT (% BY VOLUME).....
 AUTO-IGNITION TEMPERATURE
 SPECIAL FIRE FIGHTING PROCEDURES.....

FLAMMABLE.
 DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL FOAM, WATER FOG.
 52.1 (C)
 N.AV.
 N.AV.
 >425 °C / 797 °F

UNUSUAL FIRE AND EXPLOSION HAZARDS.....
 EXPLOSION DATA.....
 SENSITIVITY TO MECHANICAL IMPACT
 SENSITIVITY TO STATIC DISCHARGE
 HAZARDOUS COMBUSTION PRODUCTS

VAPOURS FORM A FLAMMABLE/EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS. DO NOT ENTER CONFINED FIRE SPACE WITHOUT ADEQUATE PROTECTIVE CLOTHING AND AN APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. EVACUATE HAZARD AREA. USE WATER TO COOL FIRE EXPOSED CONTAINERS. CONTAINERS MAY EXPLODE IN HEAT OR FIRE. VAPOURS MAY CONCENTRATE IN CONFINED AREAS. CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOUR PRESSURE BUILD UP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE. FIGHT FIRE FROM MAXIMUM DISTANCE. ALWAYS STAY AWAY FROM ENDS OF CONTAINERS DUE TO EXPLOSIVE POTENTIAL. FLAMMABLE.
 N.AV.
 N.AV.
 N.AV.
 N.AV.
 CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

SECTION 06: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES.....

ELIMINATE ALL SOURCES OF IGNITION. ISOLATE HAZARD AREA AND RESTRICT ACCESS. TRY TO WORK UP WIND OF SPILL. AVOID DIRECT CONTACT WITH MATERIAL. SATURATED CLOTHING SHOULD BE IMMEDIATELY REMOVED TO AVOID FLAMMABILITY HAZARD. WEAR APPROPRIATE BREATHING APPARATUS (IF APPLICABLE) AND PROTECTIVE CLOTHING. STOP LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN LAND SPILLS; CONTAIN WATER SPILLS BY BOOMING. USE WATER FOG TO KNOCK DOWN VAPOURS; CONTAIN RUN-OFF. FOR LARGE SPILLS REMOVE BY MECHANICAL MEANS AND PLACE IN CONTAINERS. ABSORB RESIDUE OR SMALL SPILLS WITH ABSORBENT MATERIAL AND REMOVE TO NON-LEAKING CONTAINERS FOR DISPOSAL. RECOMMENDED MATERIALS: SAND OR EARTH. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. DISPOSE OF RECOVERED MATERIAL AS NOTED UNDER DISPOSAL CONSIDERATIONS.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES AND EQUIPMENT.....

FLAMMABLE. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS. VAPOURS MAY ACCUMULATE AND TRAVEL TO DISTANT IGNITION SOURCES AND FLASHBACK. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS

PRODUCT RESIDUES. FIXED EQUIPMENT AS WELL AS TRANSFER CONTAINERS AND EQUIPMENT SHOULD BE GROUNDED TO PREVENT ACCUMULATION OF STATIC CHARGE. HOT SURFACES MAY BE SUFFICIENT TO IGNITE LIQUID EVEN IN THE ABSENCE OF SPARKS OR FLAMES. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER SOURCES OF IGNITION PRIOR TO USE AND UNTIL ALL VAPOURS ARE GONE. DO NOT PRESSURIZE DRUM CONTAINERS TO EMPTY THEM. AVOID BREATHING VAPORS AND PROLONGED OR REPEATED CONTACT WITH SKIN. LAUNDRER CONTAMINATED CLOTHING PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE. AIR-DRY CONTAMINATED CLOTHING IN A WELL VENTILATED AREA BEFORE LAUNDERING. AVOID FREQUENT OPENING AND CLOSING OF CONTAINERS AND REPEATED EXPOSURE TO AIR AS EXPLOSIVE PEROXIDES MAY BE FORMED.

STORAGE REQUIREMENTS.....

STORE IN A COOL, DRY, WELL VENTILATED AREA, AWAY FROM HEAT AND IGNITION SOURCES. USE EXPLOSION PROOF VENTILATION TO PREVENT VAPOUR ACCUMULATION. CAN ATTACK ALUMINUM AT ELEVATED TEMPERATURE.

SECTION 08: EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROL.....

MECHANICAL VENTILATION IS RECOMMENDED FOR ALL INDOOR SITUATIONS TO CONTROL FUGITIVE EMISSIONS. ELECTRICAL AND MECHANICAL EQUIPMENT SHOULD BE EXPLOSION-PROOF. CONCENTRATIONS IN AIR SHOULD BE MAINTAINED BELOW THE RECOMMENDED THRESHOLD LIMIT VALUE IF UNPROTECTED PERSONNEL ARE INVOLVED. MAKE-UP AIR SHOULD ALWAYS BE SUPPLIED TO BALANCE AIR EXHAUSTED (EITHER GENERALLY OR LOCALLY). LOCAL VENTILATION RECOMMENDED WHERE MECHANICAL VENTILATION IS INEFFECTIVE IN CONTROLLING AIRBORNE CONCENTRATIONS BELOW THE RECOMMENDED OCCUPATIONAL EXPOSURE LIMIT. FOR PERSONNEL ENTRY INTO CONFINED SPACES (I.E. BULK STORAGE TANKS) A PROPER CONFINED SPACE ENTRY PROCEDURE MUST BE FOLLOWED INCLUDING VENTILATION AND TESTING OF TANK ATMOSPHERE.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION

IMPERVIOUS CLOTHING (APRON, COVERALLS) SHOULD ALSO WORN IN CONFINED WORKSPACES OR WHERE THE RISK OF SKIN EXPOSURE IS MUCH HIGHER.

EYE/FACE PROTECTION

CHEMICAL SAFETY GOGGLES SHOULD BE WORN.

RESPIRATORY PROTECTION

IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE AN APPROPRIATE NIOSH-APPROVED RESPIRATOR. USE A NIOSH-APPROVED CHEMICAL CARTRIDGE RESPIRATOR WITH ORGANIC VAPOUR CARTRIDGES OR USE A NIOSH-APPROVED SUPPLIED-AIR RESPIRATOR. FOR HIGH AIRBORNE CONCENTRATIONS, USE A NIOSH-APPROVED SUPPLIED-AIR RESPIRATOR, EITHER SELF-CONTAINED OR AIRLINE BREATHING APPARATUS, OPERATED IN POSITIVE PRESSURE MODE.

WORK/HYGIENE PRACTICES

PROVIDE AN EYEWASH STATION IN THE AREA. SAFETY SHOWERS SHOULD BE AVAILABLE FOR EMERGENCY USE.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE.....

LIQUID

APPEARANCE & ODOUR.....

BLUE COLOUR – APPLE ODOUR

ODOUR THRESHOLD.....

N.AV.

SPECIFIC GRAVITY.....

~ 0.990

VAPOUR PRESSURE (MMHG).....

N.AV.

VAPOUR DENSITY (AIR=1).....

N.AV.

EVAPORATION RATE.....

N.AV.

BOILING POINT.....

100°C

FREEZING/MELTING POINT

0°C

PH.....

7

SOLUBILITY IN WATER (% W/W).....

SOLUBLE.

COEFFICIENT OF WATER/OIL DISTRIBUTION

N.AV.

SECTION 10: STABILITY AND REACTIVITY

STABILITY	STABLE UNDER NORMAL OPERATING CONDITIONS.
CONDITIONS TO AVOID.....	AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL IGNITION SOURCES..
INCOMPATIBILITY (MATERIALS TO AVOID).....	AVOID CONTACT WITH STRONG OXIDIZING AGENTS AND ACIDS.
HAZARDOUS DECOMPOSITION PRODUCT.....	SEE SECTION 5.
HAZARDOUS POLYMERIZATION	WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMITS.....	ISOPROPYL ALCOHOL: 200 PPM TWA-ACGIH; 400 PPM STEL-ACGIH.
IRRITANCY OF MATERIAL	SEE SECTION 2.
LD50.....	ORAL-RAT: >4,710 MG/KG; DERMAL RABBIT: >12,870 MG/KG.
LC50.....	INHALATION-RAT: 12,000 PPM FOR 8 HOURS.
SENSITIZATION TO PRODUCT	N.AV.
CARCINOGENICITY.....	ISOPROPYL ALCOHOL TESTED NEGATIVE IN TWO MUTAGENICITY ASSAYS; THE MOUSE MICRONUCLEUS AND CHINESE HAMSTER OVARY ASSAYS.
REPRODUCTIVE TOXICITY	ISOPROPYL ALCOHOL: ONE INHALATION RAT STUDY HAS SHOWN THAT 2-PROPANOL IS FETOTOXIC (CAUSED REDUCED FETAL WEIGHT GAIN) IN THE ABSENCE OF MATERNAL TOXICITY. OTHER STUDIES HAVE SHOWN NO EFFECTS OR EFFECTS IN THE PRESENCE OF MATERNAL TOXICITY.
TERATOGENICITY.....	ISOPROPYL ALCOHOL, WHEN ADMINISTERED ORALLY TO RATS AND RABBITS, PRODUCES REDUCED FETAL BODY WEIGHTS IN RATS ONLY AT DOSES WHICH RESULT IN TREATMENT RELATED TO MATERNAL DEATHS AND PRODUCES NO INDICATION OF FETAL EFFECTS IN RABBITS EVEN AT DOSE WHICH RESULTED IN SIGNIFICANT MATERNAL MORTALITY. ISOPROPYL ALCOHOL PRODUCES NO EVIDENCE OF DEVELOPMENTAL NEUROTOXICITY.
MUTAGENICITY	N.AV.
TOXICOLOGICAL SYNERGISTIC PRODUCTS.....	N.AV.
CHRONIC TOXICITY	N.AV.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION	N.AV.
------------------------------	-------

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL.....	IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS.
---------------------	---

SECTION 14: TRANSPORT INFORMATION

PROPER SHIPPING NAME.....	NOT REGULATED
TDG CLASSIFICATION	
UN NUMBER	
PACKGING GROUP	

SECTION 15: REGULATORY INFORMATION

WHMIS CLASSIFICATION	B2, D2B
CPR COMPLIANCE.....	THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

PREPARATION INFORMATION	PREPARED BY: REGULATORY AFFAIRS, TELEPHONE - (613)-744-8896 PREPARATION DATE: JULY 1, 2016
-------------------------------	---

N.AV. = NOT AVAILABLE
N.AP. = NOT APPLICABLE